

FOLDING PORTABLE CELLULAR PHONE

Background of the Invention

Field of the Invention

5 The present invention relates to a folding portable cellular phone, and relates in particular to a folding portable cellular phone wherein, in order not to expose metal externally, an external part is formed of a material (e.g., a resin) other than metal, and metal parts that are stronger than the external part are used as a skeleton
10 portion of a folded structure, so that productivity is improved.

Further, the present invention relates in particular to a folding portable cellular phone wherein, in order to improve productivity, a reinforcing part (e.g.,
15 made of metal) that is stronger than an outer part (e.g., made of resin) is used only at a skeleton portion of a folded structure, while no metal is exposed on the exterior.

Description of the Related Art

QMS
was
AI
20 ~~A feature of the conventional portable cellular phones disclosed in JP-A-9-236951 and JP-A-11-87940 is the use of a light but strong metal, such as magnesium, to form the outer exposed portion of a box-shaped member.~~

However, when metal parts are employed for the exterior of such an object, the manufacturing process part
25 yield is low, since the metal parts are not appropriate for

mass production. Further, because of the low yield, the manufacturing costs are increased.

In addition, a special part is required for shielding electric parts that are mounted on a substrate, such as a PCB (Printing Circuit Board), especially when shielding is required in the vicinity of a high frequency circuit that controls signal transmission and reception.

As another aspect, generally, multiple procedures, such as rust prevention, conversion treatment and visual painting, must be performed in order to use light, strong parts made of a metal, such as magnesium, for the external appearance of the box member. Since the defects, such as sink marks (pitting), crinkling (a corrugated defect), an uneven underlayer and an uneven color, are not found until visible painting and rust prevention have been completed, manufacturing yield is low. Further, since the metal part is employed to provide the external appearance of the box member, manufacturing costs are increased.

Summary of the Invention

To resolve this problem, a first object of the present invention is to provide a folding portable cellular phone wherein, in order not to expose metal externally, an external part is formed of a material (e.g., a resin) other than metal, and metal parts that are stronger than the external part are used as the skeleton portion of a folded

machined metal is employed for parts other than the external parts, manufacturing the external parts will be easy, and a high yield will be obtained.

According to a third aspect of the invention, in
5 the folding portable cellular phone of the first aspect, the chassis supports a substrate on which electric parts are mounted.

With this arrangement, the substrates can be supported by the chassis for which the hinges are
10 integrally formed.

According to a fourth aspect of the invention, in the folding portable cellular phone of the first aspect, the chassis functions as an electromagnetic absorption member and absorbs an unwanted electromagnetic wave.

With this arrangement, since the chassis provides
15 an electromagnetic wave absorption function, an independent shielding part is not required.

According to a fifth aspect of the invention, in the folding portable cellular phone of one of the first to
20 fourth aspects, the chassis is used as an antenna ground plate, and a hole formed in the antenna ground plate is used to mount the antenna on a substrate.

With this arrangement, an incorporated antenna can be easily provided.

According to a sixth aspect of the invention, in
25 the folding portable cellular phone of the first aspect, a

unit connector is provided between portions of the hinges, which are integrally formed with the chassis, to electrically connect the first box member and the second box member.

5 With this arrangement, a satisfactory space can be obtained in which the unit connector can be provided.

 According to a seventh aspect of the invention, in the folding portable cellular phone of the sixth aspect, the unit connector is constituted by a flexible substrate and a coaxial cable.

10 With this arrangement, the flexible substrate and the coaxial cable can be freely inserted.

 According to an eighth aspect of the invention, in the folding portable cellular phone of the first aspect, in order to cover the hinges, hinge covers, which are composed of the same material as the external parts, are provided for the first box member and the second box member.

15 With this arrangement, since the shaft of the hinge is not externally exposed, no limitations are placed on the design of the portable cellular phone, and accordingly, various models can be easily developed.

 According to a ninth aspect of the present invention, a first box member including a receiver and a second box member including a transmitter are rotated relative to each other at hinges to permit the folding of said portable cellular phone. One or both of said hinges

of said first box member and said second box member are made of reinforcing parts that are stronger than external parts and that reinforce said external parts.

According to this arrangement, since a reinforcing
5 part, which is stronger than and reinforces the external
parts is used for one or both of the hinges, the external
parts can be produced at a high yield.

According to a tenth aspect of the invention, in the folding portable cellular phone of the ninth aspect, said external parts are at least one of an upper cover of
10 said first box member and a lower cover of said second box member. The reinforcing parts are an upper hinge frame and a lower hinge frame, both including hinge portions provided respectively for said first and second box members.

15 According to this arrangement, since the reinforcing parts are used only for the hinge frames, the external parts are produced at a high yield.

According to an eleventh aspect of the invention,
in the folding portable cellular phone of the tenth aspect,
the upper hinge frame and said lower hinge frame are
20 inserted into said external parts.

With this arrangement, the hinge frames can easily be formed for the external parts by insert molding.

According to a twelfth aspect of the invention , in
25 the folding portable cellular phone of the tenth aspect,
said upper hinge frame and said lower hinge frame are

integrally formed with a chassis that supports a substrate.

With this arrangement, the hinge frame and the chassis can be integrally formed.

According to a thirteenth aspect of the invention,
5 in the folding portable cellular phone of the twelfth aspect, said chassis functions as an electromagnetic wave absorption member for absorbing an unwanted electromagnetic wave.

With this arrangement, the hinge frame and the
10 chassis are integrally formed and the electromagnetic wave absorption function can be provided for the chassis.

According to a fourteenth aspect of the invention,
in the folding portable cellular phone of the twelfth aspect, a rib is formed on said chassis in order to prevent
15 the leakage of light at a portion in which said external parts engage.

With this arrangement, when the portable cellular phone is folded, the leakage of light can be prevented at the gap between the case covers, i.e., the portion whereat
20 the external parts engage.

According to a fifteenth aspect of the invention,
in the folding portable cellular phone of the twelfth aspect, a rib is formed around said chassis to reinforce said external parts that constitute said box members.

25 With this arrangement, the strength of the external parts, such as a case and a cover, can be increased.

[illegible]

5

5

0

9

chassis that support the substrate.

Fig. 9(a) is a diagram showing the structure when a first reinforcing rib, which has a C shape, is formed around a chassis to reinforce exterior parts that constitute a box member.

Fig. 9(b) is a diagram showing the structure when a second reinforcing rib, which has an H shape, is formed around a chassis to reinforce external parts that constitute a box member.

Fig. 10(a) is a diagram showing the structure when a reinforcing rib, which has a C shape, is formed around a chassis and holes are formed in the chassis.

Fig. 10(b) is a diagram showing the structure when a second reinforcing rib, which has an H shape, is formed around a chassis and holes are formed in the chassis.

Fig. 11 is an exploded perspective view of a structure for the folding portable cellular phone of the invention that differs from the one in Fig. 6.

Detailed Description of the Preferred Embodiments

Preferred embodiments of the present invention will now be described while referring to the drawings.

Fig. 1 is an exploded perspective view of the configuration of a folding portable cellular phone according to the embodiment. In Fig. 1, the folding portable cellular phone comprises external parts, such as a

cover and a case, and an upper substrate on which electric parts are mounted, and first and second box members for which portions of a hinge are provided.

In this embodiment, the side including a receiver and a display unit (neither of which is shown) is defined as the first box member, and the side including a transmitter and a key console unit (neither of which is shown) is defined as the second box member.

The first and the second box members is coupled by the hinge, and the hinge, by permitting the two members to pivot with each other, enable the folding of the portable cellular phone at the hinge.

In Fig. 1, the first box member includes: an upper case 12, which has a window 11 for the display unit (not shown) and includes a hinge cover 13; an upper substrate 14, which is a PCB (Printing Circuit Board) on which electric parts (not shown) are mounted; an upper chassis 15, which constitutes a part of a skeleton and with which hinged portions 32 are integrally formed; and an upper cover 16, on which these components are mounted and which includes a hinge cover 17. The upper case 12 constitutes the external portion that, as a part of a portable cellular phone, attracts user attention. As for the skeleton, the upper chassis 15, with which the hinge portions 32 are integrally formed, is fixed to the upper case 12 by means such as screws or pawls.

Further, in Fig. 1, the second box member includes:
a lower cover 22, which has a hinge cover 23 in which key
holes 21 are formed to provide a key console unit (not
shown); a lower substrate 24, which is a PCB (Printing
5 Circuit Board) on which electric parts (not shown) are
mounted; a lower chassis 25, which constitutes a part of
the skeleton and which is integrally formed with hinged
portions 32; and a lower case 26, which has a hinge cover
27 and on which these components are mounted. The lower
10 case 22 is the external portion that, as a part of a
portable cellular phone, attracts user attention. As for
the skeleton, the lower chassis 25, with which the hinged
portions 32 are integrally formed, is secured to the lower
cover 22 by means such as screws or pawls.

15 In Fig. 1, hinges 31 are provided as parts
associated with the right and left hinged portions 32.
Further, a space is defined between the hinged portions 32
in order to permit the insertion of unit connectors (not
shown) that electrically connect the upper substrate 14 and
20 the lower substrate 24. The unit connectors are a flexible
substrate and a coaxial cable.

Fig. 2 is a cross-sectional view of the folding
portable cellular phone in Fig. 1 when it is closed, and
Fig. 3 is a cross-sectional view of the folding portable
25 cellular phone in Fig. 1 when it is open. As is apparent
from Figs. 2 and 3, the upper chassis 15 and the hinged

portions 32 are integrally formed, as are the lower chassis 25 and the hinged portions 32, and a substrate is mounted on each chassis.

5 Figs. 4(a) and 4(b) are diagrams showing the structures of the chassis, which are integrally formed with hinge portions 32, as the skeletons of the first and the second box members. In Fig. 4(a), the structure of the upper chassis 15 and the lower chassis 25 is shown with the hinges 31 removed. In Fig. 4(b), the structure of the
10 upper chassis 15 and the lower chassis 25 is shown with the hinges 31 attached.

Fig. 5 is a diagram showing the state wherein an antenna is incorporated in the structure shown in Fig. 1. In Fig. 5, a hole is formed in a part of the upper chassis 15, and an antenna 51 is attached to the upper substrate 14
15 via an antenna ground plate 52.

In a conventional structure, since the upper cover is made of metal, and since the metal portion is located on the antenna plate side when antenna components are
20 incorporated inside the box member, the antenna characteristics are adversely affected. However, according to the invention, since the chassis is employed to provide strength for the hinged portion, the upper cover need not be used to provide the strength for the hinged portion.
25 Thus, the upper cover can be made of a non-metallic material (e.g., a resin), so that a portable cellular phone

can be provided which exhibits superior antenna characteristics.

Fig. 6 is an exploded perspective view of the configuration of a folding portable cellular phone according to another embodiment of the invention. In Fig. 6, the folding portable cellular phone comprises external parts, such as a cover and a case, an upper substrate on which electric parts are mounted, and first and second box members provided with a hinge.

In this embodiment, the side wherein there are a receiver and a display unit (neither of them shown) is defined as the first box member, and the side wherein there are a transmitter and a key console unit (neither of them shown) is defined as the second box member.

The first and the second box members are coupled together by the hinge, and pivot relative to each other at the hinge to fold the portable cellular phone.

In Fig. 6, the first box member includes: an upper case 112, having a window 111 for the display unit (not shown); an upper substrate 113, which is a PCB (Printing Circuit Board) on which electric parts (not shown) are mounted; an upper hinge frame 114; and an upper cover 115, on which these components are mounted. The upper case 112 is the external part that, as a part of a portable cellular phone, attracts user attention. Although not shown, the upper hinge frame 114 may be formed by inserting it into

the upper case 112, or may be fixed to the upper cover 115 by means such as screws or pawls.

Further, in Fig. 6, the second box member includes:

a lower cover 122, in which key holes 121 are formed to provide a key console unit (not shown); a lower substrate 123, which is a PCB (Printing Circuit Board) on which electric parts (not shown) are mounted; a lower hinge frame 124; and a lower case 125, on which these components are mounted. The lower cover 122 is the external part that, as a part of the portable cellular phone, attracts user attention. Although not shown, the lower hinge frame 124 may be formed by inserting it into the lower cover 122, or may be fixed to the lower case 125 by means such as screws or pawls.

In Fig. 6, a shaft 131, E-shaped snap rings 132 and 133, and a hinge 134 are provided as hinge associated components in order to couple the upper hinge frame 114 and the lower hinge frame 124. In addition, a flexible substrate 135 is provided to electrically connect the upper substrate 113 and the lower substrate 123.

Fig. 7 is a diagram showing an example, unlike the one shown in Fig. 6, wherein the hinge frames in Fig. 6 are integrally formed with the chassis that support the substrates. Specifically, in Fig. 7, a hinge 142 is integrally formed with an upper chassis 143, and a hinge 142 is integrally formed with a lower chassis 144. The

upper chassis 143 is inserted between the upper case 112 and the upper substrate 113 in Fig. 6, and the lower chassis 144 is inserted between the lower cover 122 and the lower substrate 123 in Fig. 6. With this arrangement, the strength of the external parts can be even more increased. Furthermore, the upper and the lower chassis 143 and 144 function as electromagnetic wave absorption members (shields) for absorbing unwanted electromagnetic waves.

Fig. 8 is a diagram showing an example wherein light leak prevention ribs 151 are formed on the structure where, as in Fig. 7, the hinge frame is integrally formed with the chassis that supports the substrate. Since light leakage tends to occur at the gap between the case covers when the portable cellular phone is folded, the ribs 151 need only be formed at a tongue-and-groove gap, so that at the portion whereat the exterior parts are engaged the leakage of light can be prevented.

Figs. 9(a) and 9(b) are diagrams showing the structures when ribs are formed around two chassis to reinforce the external parts that constitute each box member. In Fig. 9(a), a first reinforcing rib 161, which has a C shape, is formed around a chassis 162, and in Fig. 9(b), a second reinforcing rib 163, which has an H shape, is formed around a chassis 164. With this arrangement, the strength of external parts, such as a case or a cover, can be increased.

